

# LONG LIFE LOW BAY

60,000 hour long life inductive low bay with instant restrike



High specification low bay fitting with the additional feature of a removable metal back plate, complete with snap fit connector to allow mains wiring connection prior to installation.

Rigid body, for surface or suspended applications is the ideal choice for competitive commercial and industrial applications.



## HIGH SPECIFICATION LOWBAYS - IP22

product description	part no.
endura 100w / 8000 lumen	SM100/8
endura 100w / 11000 lumen	SM100/11
100w lamp / 150w gear	

## TECHNICAL SPECIFICATIONS

<b>ratings:</b>	IP22 $\nabla$ $\blacklozenge$ CE CL I
<b>housing &amp; frame:</b>	zinc steel
<b>diffusers:</b>	safety glass or polycarbonate
<b>reflectors:</b>	anodised polished aluminium
<b>control gear:</b>	osram qt endura 100 - 150
<b>supply:</b>	slide in gear tray
<b>standards:</b>	compliance with en 60598 IP22

## ACCESSORIES

product description	part no.
1. wire guard	lbwg
2. prismatic polycarbonate dished diffuser	lbd
steel screen louvre	lbi
clear polycarbonate dished diffuser	lbcd
toughened bs glass visor	lbg

## product pictographs

