





Professional IP67 floodlight that incorporates the Osram Endura Lumilux lamp and Osram Quicktronic electronic control gear with options of 70W and 100W. With lumen outputs from 6,500 to 8,000 and instant restrike. The lamps are guaranteed for 60,000 hours continuous use with ultra low energy power consumption, due to the extended lamp life this product is ideal for installations where re-lamping is expensive such as outdoor lighting, factory and tunnel lighting.

The floodlight body and frame are manufactured from high quality thermo plastic UV and heat stabilised. The standard colour is black but also available in a choice of vibrant RAL colour options. For dusk to dawn operation built in photocell versions are available.





 E.1 - Endura energy



DESCRIPTION	LAMP	Wt.(kg)	WHITE	SILVER
<b>SYMMETRIC REFLECTOR</b> POLYCARBONATE IP67				
<b>ENDURA</b>				
70W - BLACK	E.1	5.30		
100W - BLACK	E.2	5.60		

**PC** PHOTOCELL OPTIONS ARE AVAILABLE ON ALL TYPES, TO ORDER SUFFIX CODE WITH /PC



**TECHNICAL SPECIFICATION**

HOUSING & FRAME	Flame retardant UV stabilised polycarbonate
DIFFUSERS	Toughened safety glass
PHOTOCELL	Photozell available for all types
REFLECTORS	Symmetric anodised polished aluminium
CONTROL GEAR	Osram Quicktronic Endura 100W and 150W
SUPPLY	Hinged front cover opening
COLOURS	Black RAL 9011, Silver RAL 7000, White RAL 9003

**WINDAGE** SCX=0.21M<sup>2</sup>

**ACCESSORIES**

- Steel wire guard
- Steel screen louvre
- Visor
- Spare glass
- Timed Ignitors