








Highly efficient floodlights featuring a modern, attractive design profile. Available in a wide range of light sources and high performance photometrics including a choice of symmetrical, asymmetrical and circular narrow beam versions. Suitable for many applications including extreme weather conditions and climates where both high and low temperatures are experienced. For dusk to dawn operation, photocell versions are available for all types.





— Transverse Axis
- - - Lamp Axis



- S.1 - SON-E (E27) Internal ignitor
- S.2 - SON-T (E27) External ignitor
- M.1 - MBF/U (E27)
- H.1 - Metal Halide (Rx7s)
- CF.4 - Compact fluorescent, 2 pin, (GX24d-3), 26W - triple
- CF.5 - Compact fluorescent, 4 pin, (GX24q-3), 32W - triple
- CF.6 - Compact fluorescent, 4 pin, (GX24q-4), 42W - triple



TECHNICAL SPECIFICATION

HOUSING & FRAME	Thermo-plastic polycarbonate
DIFFUSERS	Standard glass or polycarbonate
PHOTOCELL	Available for all types
REFLECTORS	Anodised polished aluminium
CONTROL GEAR	Available with a wide variety of options
SUPPLY ACCESS	Hinged front cover opening
EQUIPMENT	Corrosion proof and anti-seizure
STANDARDS	Certified to EN 60598 IP65
COLOURS	Black RAL 9011, Silver RAL 7000, White RAL 9003

WINDAGE SCX=0.110M²

ACCESSORIES

- Steel wire guard
- Steel screen louvre
- Visor
- Screen printed spare glass
- Wire mesh protective cage
- Colour tinted glass lens (special order)
- Timed Igniters



DESCRIPTION	LAMP	Wt.(kg)	WHITE	SILVER
-------------	------	---------	-------	--------

SYMMETRIC REFLECTOR WIDE BEAM POLYCARBONATE IP65

HIGH PRESSURE SODIUM

50W - BLACK	S.1	3.90
70W - BLACK	S.1	3.90
50W - BLACK	S.2	3.90
70W - BLACK	S.2	3.90

MERCURY BLENDED FLU.

50W - BLACK	M.1	3.90
80W - BLACK	M.1	3.90
125W - BLACK	M.1	3.93

METAL HALIDE

70W - BLACK	H.1	4.00
150W - BLACK	H.1	4.00

COMPACT FLUORESCENT

26W - BLACK S/START	CF.4	3.00
26W - BLACK HF	CF.5	3.10
32W - BLACK HF	CF.5	3.10
42W - BLACK HF	CF.6	3.20

NB: SYMMETRIC NARROW BEAM VERSIONS ALSO AVAILABLE, TO ORDER INSERT 'N' IN THE CODE

ASYMMETRIC REFLECTOR WIDE BEAM POLYCARBONATE IP65

HIGH PRESSURE SODIUM

50W - BLACK	S.2	3.90
70W - BLACK	S.2	3.92

METAL HALIDE

70W - BLACK	H.1	4.00
-------------	-----	------



CIRCULAR PROJECTOR 30° POLYCARBONATE IP65

METAL HALIDE

70W - BLACK	H.1	4.00
150W - BLACK	H.1	4.30



POLYCARBONATE LENS POLYCARBONATE IP65

HIGH PRESSURE SODIUM

50W - BLACK	S.1	4.10
70W - BLACK	S.1	4.20

MERCURY BLENDED FLU.

50W - BLACK	M.1	4.05
80W - BLACK	M.1	4.05

METAL HALIDE

70W - BLACK	H.1	4.20
150W * - BLACK	H.1	4.30



PC PHOTOCELL OPTIONS ARE AVAILABLE ON ALL TYPES, TO ORDER SUFFIX CODE WITH /PC

* 150W Polycarbonate lens unit for down lighting only
NB: A timed ignitor must be used with a ceramic lamp