





General purpose floodlight that features a high impact anticorrosive polycarbonate lens and body. Integral control gear and also available complete with lamp which makes this floodlight speedy and simple to install. Standard body colours are Black, White or Silver Grey. Suitable for all types of applications and weather conditions. For dusk to dawn operation photocell versions are available for all types.





- S.1 - SON-E Δ (E27) Internal ignitor
- H.1 - Metal Halide (RX7s)
- H.3 - Metal Halide (E27)
- CF.4 - Compact fluorescent, 2 pin, (GX24d-3) - triple
- CF.5 - Compact fluorescent, 4 pin, (GX24d-4) - triple
- CF.6 - Compact fluorescent, 4 pin, (GX24q-4), 42W - triple
- M.1 - MBF/U (E27)



DESCRIPTION	LAMP	Wt.(kg)	WHITE	SILVER
SYMMETRIC REFLECTOR POLYCARBONATE IP65				
HIGH PRESSURE SODIUM Δ 70W - BLACK	S.1	3.90		
METAL HALIDE 70W - BLACK	H.1	3.90		
100W - BLACK E27	H.3	3.90		
COMPACT FLUORESCENT 26W - BLACK - S/START	CF.4	3.90		
32W - BLACK HF	CF.5	3.90		
42W - BLACK HF	CF.6	3.20		
2X 26W - BLACK HF*	CF.5	3.90		
2X 32W - BLACK HF*	CF.5	3.90		
MERCURY BLENDED FLU. 80W - BLACK	M.1	3.90		

PC PHOTOCCELL OPTIONS ARE AVAILABLE ON ALL TYPES, TO ORDER SUFFIX CODE WITH /PC

*Twin HF Ballast Unit
NB: A timed ignitor must be used with a ceramic lamp

TECHNICAL SPECIFICATION

HOUSING & FRAME	Thermo-plastic polycarbonate
DIFFUSERS	Polycarbonate
PHOTOCCELL	Photocell available for all types
REFLECTORS	Anodised polished aluminium
CONTROL GEAR	Available with a wide variety of options
SUPPLY ACCESS	Hinged front cover opening
COLOURS	Black RAL 9011, Silver RAL 7000, White RAL 9003

WINDAGE SCX=0.11M2

